



The classic **1965Z0 MityLite™** has been discontinued.
The **1975Z0 MityLite™** is the suggested replacement.

Light comparison:

Feature	1965Z0	1975Z0
		
Colour	HiViz Yellow	HiViz Yellow
Length, mm	139	146
Weight w/ batteries, g	54	54
Weight w/o batteries, g	31	28
Body	Anti-static Impact Modified PC/PBT	Anti-static Impact Modified PC/PBT
O-Ring	EPDM	NBR
Lens	Polycarbonate (PC)	Polycarbonate (PC)
Shroud	Anti-static Impact Modified PC/PBT	Anti-static Impact Modified PC/PBT
Lumens	87	117
Runtime	2h30m	2h15m
Beam angle	41m	24m
IP rating	IPX7	IP68
Batteries	2xAAA	2xAAA
Switch	Rotary	Momentary Push Button
Light modes	On/Off	On/Off

Key benefits of the 1975Z0 compared to the 1965Z0:

- 25% boost of light output (from 87 to 117) while the runtime has been shortened by 10% only
- Higher IP rating, which extends list of applications
- O-ring made from NBR, which has good resistance to gasoline, diesel fuel, motor oil, acids and non-polar solvents and thus it is suitable for heavy-duty applications